

# DHL22-F600

## Full-HD LCD Monitor



### Product Features

- Full HD 1920\*1080 resolution
- 1ch HDMI & 1ch VGA input
- Support 1ch audio input
- Built-in speaker

### Technical Specifications

|                                    |   |
|------------------------------------|---|
| <b>Model</b>                       | <b>DHL22-F600</b>                       |
| <b>System</b>                      |   |
| Diagonal                           | 20.7"(16:9)                             |
| Backlight                          | WLED                                    |
| Resolution                         | 1920x1080                               |
| Luminance(Standard)                | 200cd/m <sup>2</sup>                    |
| Contrast                           | 600:1                                   |
| Angle of view                      | 130°/178° (vertical / horizontal)       |
| Response Time(Grey Scale)          | 4ms                                     |
| <b>Video &amp; Audio Interafce</b> |   |
| PC Signal                          | VGA(D-Sub)x1                            |
| Digital Signal                     | HDMIx1(1920x1080) , downward compatible |
| Audio Input                        | Audio Input x 1 (3.5mm)                 |

## DHL22-F600

|                              |                               |
|------------------------------|-------------------------------|
| Audio Output                 | Speaker                       |
| <b>General</b>               |                               |
| Power Consumption (Standard) | 23W                           |
| Power Consumption (Standby)  | ≤0.5W                         |
| Power Supply                 | AC100-240V~(+/-10%), 50/60 Hz |
| Bezel Color                  | Black                         |
| Gross Weight                 | 2.5±0.3kg                     |
| Unit Dimensions(mm)          | 490.30×292.30×48.30           |
| Installation Mode            | Equipped with pedestal        |
| VESA Standard                | VESA 100mm*100mm              |
| Working Temperature          | 0°C~40°C                      |
| Working Humidity             | 10%~90%                       |
| Stock Temperature            | -20°C~60°C                    |
| Accessory                    | VGA cable, Power cable        |

